

HOSES FOR ROOM #1

NOTE: HOSES (E) AND (F) ARE INCLUDED WITH THE ROOM EXTENSION MECHANISM

- |  |  |
|--|--|
| <p>(A) .25" ID HOSE ASSY<br/>ROD END - ALWAYS PRESSURIZED</p> <p>(B) .25" ID HOSE ASSY<br/>CAP END (ROOM)</p> <p>(C) 03 HOSE ASSY<br/>ROD END - ALWAYS PRESSURIZED -<br/>HOSES MUST MAINTAIN EQUAL<br/>LENGTH AND DIAMETER</p> <p>(D) .25" ID HOSE ASSY<br/>CAP END - HOSES MUST MAINTAIN<br/>EQUAL LENGTH AND DIAMETER</p> <p>(E) AP24632 HOSE ASSY HWH02HP x 48"<br/>ROD END - ALWAYS PRESSURIZED -<br/>HOSES MUST MAINTAIN EQUAL<br/>LENGTH AND DIAMETER</p> <p>(F) AP24818 HOSE ASSY HWH02HP x 86"<br/>CAP END - MUST MAINTAIN EQUAL<br/>LENGTH AND DIAMETER</p> | <p>(I) .25" ID HOSE ASSY<br/>CAP END (LIFT)</p> <p>(J) .25" ID HOSE ASSY<br/>CAP END (ROOM)</p> <p>(K) .25" ID HOSE ASSY<br/>CAP END (ROOM)</p> <p>(L) .25" ID HOSE ASSY ROD END (LIFT)<br/>ALWAYS PRESSURIZED</p> <p>(M) .25" ID HOSE ASSY<br/>CAP END (LIFT)</p> <p>(N) .25" ID HOSE ASSY<br/>ROD END - ALWAYS PRESSURIZED (LIFT)</p> <p>(O) .25" ID HOSE ASSY ROD END (LIFT)<br/>ALWAYS PRESSURIZED</p> <p>(P) .25" ID HOSE ASSY<br/>CAP END LIFT</p> |
|--|--|

NOTE: INSTALLATION MUST CONFORM TO GOOD SHOP PRACTICES, SAE STANDARDS, RVIA STANDARDS, AND OTHER APPLICABLE STANDARDS.

CONTROL PACKAGE: AP51399

		HWH I-80 EXIT 267 SOUTH RT 1 MOSCOW, IOWA 52760	
		SCALE 1:6	DATE 22APR13
		DRAWN BY .	
		HYD CONN DIAGRAM	
NO.	DATE	REVISION	
		ITB	
		DRAWING NUMBER MP70627 A/B	

THE INFORMATION DISCLOSED ON THIS DRAWING IS CONFIDENTIAL AND MUST NOT BE DISCLOSED OR USED IN ANY MANNER WHICH WILL BE DETRIMENTAL TO THE HWH CORPORATION

