On I-80, Exit 267 South) | 2096 Moscow Road | Moscow, Iowa 52760
Phone: (800)321-3494 or (563)724-3396 | **Fax:** (563)724-3408 | **Web**: www.HWH.com

REQUIREMENTS FOR USING HWHÒ ENVIRONMENTAL AIR SEALS and Limited Warranty Information

- The gap between the air seal mounting track and the room is nominally 3/8 inch and must be no more than 1/2 inch around the entire room.

- HWH® provides all controls, including a regulator and vacuum assembly, for each air seal assembly.
  - Maximum pressure in seal is 12 psi.
  - Vacuum shall be 20 inHg or deeper.

- Training is necessary to successfully install HWH® air seals.

- HWH® recommends that rooms are designed to move into vehicle for air seal replacement. Typically, the room must retract at least four inches into the vehicle (from the normal retracted position) to allow for seal replacement from outside vehicle.

- Limited Warranty on air seals assemblies is **one (1) year** due to HWH® manufacturing defects or material defects.

- If HWH® determines an air seal assembly is eligible for warranty:
  - HWH® will provide replacement seal assembly.
  - HWH® will pay up to eight (8) hours of labor to replace seal assembly.

Please acknowledge having received this statement.			
Print Name:			
Title:			
Company Name:			
Signature:		**Date:** *(mm/dd/yyyy)*	